

Gov Notes

Links and notes.

- [2025 Payroll Calendar](#)
- [Removing Cisco Config Commands](#)

2025 Payroll Calendar



2025

JANUARY

PP#	S	M	T	W	T	F	S
2				1	2	3	4
	5	6	7	8	9	10	11
3	12	13	14	15	16	17	18
	19	20	21	22	23	24	25
4	26	27	28	29	30	31	

FEBRUARY

PP#	S	M	T	W	T	F	S
							1
	2	3	4	5	6	7	8
5	9	10	11	12	13	14	15
	16	17	18	19	20	21	22
6	23	24	25	26	27	28	

MARCH

PP#	S	M	T	W	T	F	S
							1
	2	3	4	5	6	7	8
7	9	10	11	12	13	14	15
	16	17	18	19	20	21	22
8	23	24	25	26	27	28	29
	30	31					

APRIL

PP#	S	M	T	W	T	F	S
			1	2	3	4	5
9	6	7	8	9	10	11	12
	13	14	15	16	17	18	19
10	20	21	22	23	24	25	26
	27	28	29	30			

MAY

PP#	S	M	T	W	T	F	S
						1	2
						3	
11	4	5	6	7	8	9	10
	11	12	13	14	15	16	17
12	18	19	20	21	22	23	24
	25	26	27	28	29	30	31

JUNE

PP#	S	M	T	W	T	F	S
13	1	2	3	4	5	6	7
	8	9	10	11	12	13	14
14	15	16	17	18	19	20	21
	22	23	24	25	26	27	28
15	29	30					

JULY

PP#	S	M	T	W	T	F	S
			1	2	3	4	5
	6	7	8	9	10	11	12
16	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
17	27	28	29	30	31		

AUGUST

PP#	S	M	T	W	T	F	S
						1	2
	3	4	5	6	7	8	9
18	10	11	12	13	14	15	16
	17	18	19	20	21	22	23
19	24	25	26	27	28	29	30
	31						

SEPTEMBER

PP#	S	M	T	W	T	F	S
			1	2	3	4	5
	6	7	8	9	10	11	12
20	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
	27	28	29	30			

OCTOBER

PP#	S	M	T	W	T	F	S
			1	2	3	4	
22	5	6	7	8	9	10	11
	12	13	14	15	16	17	18
23	19	20	21	22	23	24	25
	26	27	28	29	30	31	

NOVEMBER

PP#	S	M	T	W	T	F	S
						1	
24	2	3	4	5	6	7	8
	9	10	11	12	13	14	15
25	16	17	18	19	20	21	22
	23	24	25	26	27	28	29
26	30						

DECEMBER

PP#	S	M	T	W	T	F	S
			1	2	3	4	5
	6	7	8	9	10	11	12
	13	14	15	16	17	18	19
1	20	21	22	23	24	25	26
	27	28	29	30	31		

Removing Cisco Config Commands

Alright, let's tackle this step by step for the `mac-address sticky` command on interface Gi1/0/7.

1. Understanding the Context: The `sticky mac-address` command on an interface is typically used when you want a MAC address to remain associated with that port even if the device disconnects and reconnects. Let's verify its current setting first:

```
show running-config interface gigabitethernet 1/0/7
```

This will show us the exact configuration for this port, including any sticky MAC settings.

2. Removal Process:

Here are two approaches depending on how it was configured:

Option A - If it's a direct setting:

```
interface GigabitEthernet1/0/7
no mac-address sticky
end
```

Option B - If there's a specific MAC address defined:

```
interface GigabitEthernet1/0/7
no mac-address sticky 00-XX-XX-XX-XX-XX
end
```

(Replace XX with the actual MAC address)

3. Verification Steps:

After removing it:

- Save the configuration (`copy running-config startup-config`)
- Verify the interface status (`show interfaces gigabitethernet 1/0/7`)
- Test connectivity to ensure nothing was impacted

Important Safety Notes:

- Always save a backup before making changes
- Document all modifications in your change log
- If there's uncertainty about the command, consider temporarily disabling it instead of removing it

Would you like me to explain any part of these steps in more detail?

claude 3.5 sonnet